

HS009638473B2

(12) United States Patent

Rasmussen et al.

(54) BEVERAGE DISPENSING ASSEMBLY COMPRISING BEVERAGE DISTRIBUTION PYTHON AND A METHOD OF PRODUCING THE BEVERAGE DISTRIBUTION PYTHON

(71) Applicant: CARLSBERG BREWERIES A/S,

Copenhagen V (DK)

(72) Inventors: Jan Nørager Rasmussen, Olstykke

(DK); Steen Vesborg, Gentofte (DK)

(73) Assignee: CARLSBERG BREWERIES A/S,

Copenhagen V (DK)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 62 days.

(21) Appl. No.: 14/649,182

(22) PCT Filed: Dec. 4, 2013

(86) PCT No.: **PCT/EP2013/075532**

§ 371 (c)(1),

(2) Date: Jun. 2, 2015

(87) PCT Pub. No.: WO2014/086858

PCT Pub. Date: Jun. 12, 2014

(65) Prior Publication Data

US 2015/0308755 A1 Oct. 29, 2015

(30) Foreign Application Priority Data

Dec. 4, 2012 (EP) 12195517

(51) Int. Cl.

B67D 7/74 (2010.01)

F28F 1/10 (2006.01)

(Continued)

(52) U.S. Cl.

11/22 (2013.01);

(Continued)

(10) Patent No.: US 9,638,473 B2

(45) **Date of Patent:**

May 2, 2017

(58) Field of Classification Search

CPC B67D 1/0865; F28F 1/00; B23P 15/26; F28D 7/0008; F16L 11/22; F16L 53/00;

F16L 59/153

(Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

3,269,422 A * 8/1966 Matthews B67D 1/0867 138/111

5,094,088 A * 3/1992 Davis B67D 7/80 165/164

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0382310 8/1990 EP 1626221 2/2006

(Continued)

OTHER PUBLICATIONS

International Search Report on corresponding PCT application (PCT/EP2013/075532) from International Searching Authority (EPO) dated Aug. 26, 2014.

Primary Examiner — Lien Ngo

(74) Attorney, Agent, or Firm — Klein, O'Neill & Singh,

(57) ABSTRACT

A beverage dispensing assembly 10 comprises a beverage distribution python 18 extending between a beverage storage area and a beverage tapping area. The beverage distribution python 18 comprises a liquid carrying line defining a center line 22. The liquid carrying line comprises a beverage tube 16 and/or a beverage guide tube. The beverage distribution python 18 further comprises a pipe 34 covering the liquid carrying line in a coaxial relationship to the center line and establishing a space in-between the pipe 34 and the liquid carrying line. An insulation layer 32 comprises at least 80% aerogel by volume is located in the space between the pipe (Continued)

